

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: **Cement**

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY		
1.1 Identification of the Substance	Portland Cement, composite: CEM IV/B (P-W) 42.5N	
1.2 Relevant identified uses of the substance or mixture and uses advised against	Cements are used in industrial installations to manufacture/formulate hydraulic binders for building and construction work, such as ready-mixed concrete, mortars, renders, grouts, plasters, as well as precast concrete. Common cements and cement-containing mixtures (hydraulic binders) are used industrially, by professionals as well as by consumers in building and construction work, indoor and outdoor. The identified uses of cements and cement-containing mixtures cover the dry products and the products in a wet suspension (paste). See section 16.2 for more information regarding use descriptors and categories. Any uses not mentioned above are advised against.	
1.3 Manufacturer	Titan Sharrcem Sh. P.K Full address: St. Adem Jashari 71510 Hani Elezit, Kosovo Telephone number: 00383 290 385 500 Health and safety: bujar.aliu@sharrcem.com Environment: zenulla.burnniku@sharrcem.com Quality: teodor.zguro@sharrcem.com	
1.4 Emergency telephone	00383 38 500 600	
Other necessary telephones	Kosovo University Clinical Center (Hospital Pristina) : 00383 38 500 600 Hours of operation: 24 / 7	
2. HAZARDS IDENTIFICATION		
2.1. Classification of the substance or mixture		
2.1.1 According to regulation (EC) № 1272/2008		
Hazard class	Hazard category	Hazard statements
Skin irritation	2	H315: Causes skin irritation
Serious eye damage/eye irritation	1	H318: Causes serious eye damage

Skin sensitisation	1B	H317: May cause an allergic skin reaction
Specific target organ toxicity single exposure respiratory tract irritation	3	H335: May cause respiratory irritation

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: Cement

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

2.2 Label elements

2.2.1 According to Regulation (EC) No 1272/2008

Hazard pictograms



Hazard statements

H318	Causes serious eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H335	May cause respiratory irritation

Precautionary statements

P102: Keep out of reach of children
P264: Wash thoroughly after handling
P272: Contaminated work clothing should not be allowed out of the workplace
P280: Wear protective gloves/protective clothing/eye protection/face protection
P305+P351+P338+P310: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician
P302+P352+P333+P313: IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention
P261+P304+P340+P312: Avoid breathing dust/fume/gas/mist/vapours/spray. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
P321: Specific treatment
P362: Take off contaminated clothing and wash before reuse
P501: Dispose of contents/container according to current regulations

Supplemental information

Skin contact with wet cement, fresh concrete or mortar may cause irritation, dermatitis or burns. May cause damage to products made of aluminium or other non-noble metals.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: Cement

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

2.3. Other hazards

Cement does not meet the criteria for PBT or vPvB in accordance with Annex XIII of REACH (Regulation (EC)

No 1907/2006).

The product contains chromate reducing agent. As a result, the content of soluble chromium (VI) is less than 2

ppm. If the storage conditions are not appropriate or the storage period is exceeded, the effectiveness of the

reducing agent can diminish, and the cement can become skin sensitizing (R43 resp. H317 or EUH203).

3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1. Mixtures

Common cement types according to the EN 197-1 (Common cements) standards:

Portland cement clinker 65 -100%

Limestone – 0 -30%

Gypsum – 3 - 10%

Reducing agent – 0 – 0,5%

Grinding aid – 0 – 0,05%

Components presenting the health and environmental hazards

Constituent	% [weight]	EC No.	CAS No.	REACH Registration No. °	Classification Regulation 1272/2008	
Portland cement clinker	65-100%	266-043-4	65997-15-1	Exempted from registration	Skin irritation 2	H315
					Skin sensitisation 1B	H317
					Eye damage 1	H318
					STOT SE 3 - Specific target organ toxicity-single vexposure	H335
					Skin irritation 2	H315

Flue dust	0,1-5%	270-659-9	68475-76-3	01-2119486767-17-xxxx	Skin sensitisation 1B	H317
					Eye damage	H318
					STOT SE 3 - Specific target organ toxicity-single exposure	H335
Other (reducing agent and grinding aid)	0-0,5% 0 -0,05%	Below the concentration limits set up in CLP 1272 / 2008				

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: Cement

Revised version: 1/1 June, 2017 Print date: 20 June, 2017
1/2 October 2019
1/3 June 2025

° Individual part of registration number may be omitted by the supplier of the mixture provided that:
(a) this supplier assumes the responsibility to provide the full registration number upon request for enforcement purposes, or, if the full registration number is not available to him, to forward the request to his supplier, in line with point (b).; and
(b) this supplier provides the full registration number to the Member State authority responsible for enforcement (hereinafter referred to as the "enforcement authority") within 7 days upon request, received either directly from the enforcement authority or forwarded by his recipient, or, if the full registration number is not available to him, this supplier shall forward the request to his supplier within 7 days upon request and at the same time inform the enforcement authority thereof.
This does not apply to imported mixtures.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General notes

No personal protective equipment is needed for first aid responders. First aid workers should avoid contact with wet cement or wet cement containing mixtures.

Following contact with eyes

Do not rub eyes in order to avoid possible cornea damage as a result of mechanical stress. Remove contact lenses if any. Incline head to injured eye, open the eyelid(s) widely and flush eye(s) immediately by thoroughly rinsing with plenty of clean water for at least 20 minutes to remove all particles. Avoid flushing particles into uninjured eye. If possible, use isotonic water (0.9% NaCl). Contact a specialist of occupational medicine or an eye specialist.

Following skin contact

For dry cement, remove and rinse abundantly with water.
For wet cement, wash skin with plenty of water.
Remove contaminated clothing, footwear, watches, etc. and clean thoroughly before re-using them.

Seek medical treatment in all cases of irritation or burns.

Following inhalation

Move the person to fresh air. Dust in throat and nasal passages should clear spontaneously.

Contact a

physician if irritation persists or later develops or if discomfort, coughing or other symptoms persist.

Following ingestion

Do not induce vomiting. If the person is conscious, wash out mouth with water and give plenty of water to

drink. Get immediate medical attention or contact the anti poison centre.

4.2. Most important symptoms and effects, both acute and delayed

Eyes: Eye contact with cement (dry or wet) may cause serious and potentially irreversible injuries.

Skin:

Cement may have an irritating effect on moist skin (due to sweat or humidity) after prolonged contact or may

cause contact dermatitis after repeated contact.

Prolonged skin contact with wet cement or wet concrete may cause serious burns because they develop

without pain being felt (for example when kneeling in wet concrete even when wearing trousers).

For more details see Reference (1).

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: Cement

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

Inhalation: Repeated inhalation of dust of common cements over a long period of time increases the risk of developing lung diseases.

Environment: Under normal use, common cement is not hazardous to the environment.

4.3. Indication of any immediate medical attention and special treatment needed

When contacting a physician, take this SDS with you.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Common cements are not flammable.

5.2 Special hazards arising from the substance or mixture

Cements are non-combustible and non-explosive and will not facilitate or sustain the combustion of other materials.

5.3 Advice for fire-fighters

Cement poses no fire-related hazards. No need for special protective equipment for fire fighters.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Wear protective equipment as described under Section 8 and follow the advice for safe handling and use given under Section 7.

6.1.2 For emergency responders

Emergency procedures are not required.

However, respiratory protection is needed in situations with high dust levels.

6.2 Environmental precautions

Do not wash cement down sewage and drainage systems or into bodies of water (e.g. streams).

6.3 Methods and material for containment and cleaning up

Collect the spillage in a dry state if possible.

Dry cement

- ✓ Use cleanup methods such as vacuum clean-up or vacuum extraction (Industrial portable units, equipped with high efficiency air filters (EPA and HEPA filters, EN 1822-1:2009) or equivalent technique) which do not cause airborne dispersion. Never use compressed air.
 - ✓ Alternatively, wipe-up the dust by mopping, wet brushing or by using water sprays or hoses (fine mist to avoid that the dust becomes airborne) and remove slurry. If not possible, remove by slurring with water (see wet cement).
 - ✓ When wet cleaning or vacuum cleaning is not possible and only dry cleaning with brushes can be done, ensure that the workers wear the appropriate personal protective equipment and prevent dust from spreading.
- Avoid inhalation of cement and contact with skin. Place spilled materials into a container. Solidify before disposal as described under Section 13.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: Cement

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

Wet cement

Clean up wet cement and place in a container. Allow material to dry and solidify before disposal as described under Section 13.

6.4 Reference to other sections

See sections 8 and 13 for more details.

7. HANDLING AND STORAGE

Do not handle or store near food and beverages or smoking materials.

7.1 Precautions for safe handling

7.1.1 Protective measures

Follow the recommendations as given under Section 8.

To clean up dry cement, see Subsection 6.3.

Measures to prevent fire

Not applicable.

Measures to prevent aerosol and dust generation

Do not sweep. Use dry cleanup methods such as vacuum clean-up or vacuum extraction, which do not cause airborne dispersion.

For more information, refer to the practice guidelines adopted under the Social Dialogue Agreement on

Workers' Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing

it, by Employee and Employer European sectoral associations, among which CEMBUREAU. These safe

handling practices It can be found via the following link: [http://www.nepsi.eu/agreement-good-practiceguide/](http://www.nepsi.eu/agreement-good-practiceguide/good-practice-guide.aspx)

good-practice-guide.aspx.

Measure to protect the environment

No particular measures.

7.1.2 Information on general occupational hygiene

Do not handle or store near food and beverages or smoking materials.

In dusty environment, wear dust mask and protective goggles.

Use protective gloves to avoid skin contact.

7.2 Conditions for safe storage, including any incompatibilities

Bulk cement should be stored in silos that are waterproof, dry (i.e. with internal condensation minimised),

clean and protected from contamination.

Engulfment hazard: To prevent engulfment or suffocation, do not enter a confined space, such as a silo, bin,

bulk truck, or other storage container or vessel that stores or contains cement without taking the proper

security measures. Cement can build-up or adhere to the walls of a confined space. The cement can release,

collapse or fall unexpectedly.

Packed products should be stored in unopened bags clear of the ground in cool, dry conditions and protected

from excessive draught in order to avoid degradation of quality. Bags should be stacked in a stable manner.

Do not use aluminium containers for the storage or transport of wet cement containing mixtures due to

incompatibility of the materials.

7.3 Specific end use(s)

No additional information for the specific end uses (see section 1.2).

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: Cement

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

7.4 Control of soluble Cr (VI)

For cements treated with a Cr (VI) reducing agent according to the regulations given in Section 15, the

effectiveness of the reducing agent diminishes with time. Therefore, cement bags and/or delivery documents

will contain information on the packaging date, the storage conditions and the storage period appropriate to maintaining the activity of the reducing agent and to keeping the content of soluble chromium VI below 0.0002

% of the total dry weight of the cement ready for use, according to EN 196-10. They will also indicate the appropriate storage conditions for maintaining the effectiveness of the reducing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

<i>Exposure limit values</i>	<i>Value (as 8 h TWA), mg/m³</i>	<i>Legal reference</i>
Exposure limit values for cement dust in working environment	10	No 537 of Annex I of the Ordinance No.13 /2003 regulates the workers' protection from risks related with workplace exposure to harmful chemical agents

DNEL₁ inhalation (8h): 10 mg/m³

DNEL dermal: not applicable

DNEL oral: not relevant

The DNEL refers to respirable dust.

For workers, no DNEL for dermal exposure are available, neither from human hazard studies nor from human

experience. Since cements are classified as irritating to skin and eyes, dermal exposure has to be minimised

as far as technically feasible.

PNEC₂ water: not applicable

PNEC sediment: not applicable

PNEC soil: not applicable

The risk assessment of the environmental compartments is based on the resulting pH impact on water.

Possible pH changes in surface water, ground water and STP effluent should not increase the value 9.

8.2 Exposure controls

For each individual PROC, users can choose from either option A) or B) in the table below, according to what

is best suited to their specific situation. If one option is chosen, then the same option has to be chosen in the

table from section "8.2.2 Individual protection measures such as personal protection equipment". Specification of respiratory protective equipment. Only combinations between A) – A) and B) – B) are possible.

8.2.1 Appropriate engineering controls

Measures to reduce generation of dust and to avoid dust propagating in the environment such as dedusting, exhaust ventilation and dry clean-up methods which do not cause airborne dispersion.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: **Cement**

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

A) Appropriate engineering controls - cement: inhalation DNEL of 10 mg/m³

USE	Proc*	Exposure	Localized controls	Efficiency
Industrial manufacture/formulation of hydraulic building and construction materials	2, 3	Duration is not restricted (up to 480 minutes per shift, 5 shifts a week)	not required	-
	14, 26		A) general ventilation or B) generic local exhaust ventilation	- 78 %
	5, 8b, 9		A) general ventilation or B) generic local exhaust ventilation	17 % 78 %
Industrial uses of dry hydraulic building and construction materials (indoor, outdoor)	2		not required	-
	14, 22, 26		A) not required or B) generic local exhaust ventilation	- 78 %
	5, 8b, 9		A) general ventilation or B) generic local exhaust ventilation	17 % 78 %
Industrial uses of wet suspension of hydraulic building and construction materials	7		A) not required or B) generic local exhaust ventilation	- 78 %
	2, 5, 8b, 9, 10, 13, 14		not required	-
Professional use of dry hydraulic building and construction material (indoor, outdoor)	2		not required	-
	9, 26		A) not required or B) generic local exhaust ventilation	- 72 %
	5, 8a, 8b, 14		A) not required or B) integrated local exhaust ventilation	- 87 %
	19		localised controls are not applicable, process only in good ventilated rooms or outdoor	-
Professional uses of wet suspensions of hydraulic building and construction materials	11		A) not required or B) generic local exhaust ventilation	- 72 %
	2, 5, 8a, 8b, 9, 10,		not required	-

13, 14,
19

* PROC's are identified uses and defined in section 16.2.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: Cement

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

B) Appropriate engineering controls – flue dust and clinker: the same as the cement.

C) Appropriate engineering controls - grinding aid and reducing agent: Not relevant because the

concentrations of these substances are below the concentration limits set up in the CLP 1272 / 2008

(see point 3).

8.2.2 Individual protection measures such as personal protection equipment

General: During work avoid kneeling in fresh mortar or concrete wherever possible. If kneeling is absolutely necessary then appropriate waterproof personal protective equipment must be worn. Do not eat, drink or smoke when working with cement to avoid contact with skin or mouth. Before starting to work with cement, apply a barrier creme and reapply it at regular intervals. Immediately after working with cement or cement containing materials, workers should wash or shower or use skin moisturisers. Remove contaminated clothing, footwear, watches, etc. and clean thoroughly before re-using them.

Eye/face protection



Wear approved glasses or safety goggles according to EN 166 when handling dry or wet cement to prevent contact with eyes.

Skin protection



Use watertight, wear- and alkali-resistant protective gloves (e.g. nitrile soaked cotton gloves with CE marking) internally lined with cotton; boots; closed long-sleeved protective clothing as well as skin care products (e.g. barrier creams) to protect the skin from prolonged contact with wet cement. Particular care should be taken to ensure that wet cement does not enter the boots. For the gloves, respect the maximum wearing time to avoid skin problems.

In some circumstances, such as when laying concrete or screed, waterproof trousers or kneepads are necessary.

Examinations have shown that nitrile soaked cotton gloves (layer thickness ca. 0.15 mm) with CE marking, internally lined with cotton, offer over a period of 480 min sufficient protection. Change wet gloves. Ready hold gloves for change.

Respiratory protection



When a person is potentially exposed to dust levels above exposure limits, use appropriate respiratory protection. The type of respiratory protection should be adapted to the dust level and conform to the relevant EN standard, (e.g. EN 149, EN 140, EN 14387, EN 1827) or national standard.

Thermal hazards

Not applicable.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: **Cement**

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

A) Individual protection measures such as personal protection equipment - cement: inhalation DNEL of 10 mg/m³

Use	PROC*	Exposure	Specification of respiratory protective equipment (RPE)	RPE ^a prote
Industrial manufacture/formulation of hydraulic building and construction materials	2, 3	Duration is not restricted (up to 480 minutes per shift, 5 shifts a week)	not required	-
	14, 26		A) FFP1 mask or B) not required	APF = -
	5, 8b, 9		A) FFP2 mask or B) FFP1 mask	APF = APF =
Industrial uses of dry hydraulic building and construction materials (indoor, outdoor)	2		not required	-
	14, 22, 26		A) FFP1 mask or B) not required	APF = -
	5, 8b, 9		A) FFP2 mask or B) FFP1 mask	APF = APF =
Industrial uses of wet suspension of hydraulic building and construction materials	7		A) FFP1 mask or B) not required	APF = -
	2, 5, 8b, 9, 10, 13, 14		not required	-
	2		FFP1 mask	APF =

	Professional use of dry hydraulic building and construction material (indoor, outdoor)	9, 26		A) FFP2 mask or B) FFP1 mask	APF = 10 APF = 4	
		5, 8a, 8b, 14		A) FFP3 mask or B) FFP1 mask	APF = 20 APF = 4	
		19		FFP2 mask	APF = 10	
	Professional uses of wet suspensions of hydraulic building and construction materials	11		A) FFP2 mask or B) FFP1 mask	APF = 10 APF = 4	
		2, 5, 8a, 8b, 9, 10, 13, 14, 19		not required	-	

* PROC's are identified uses and defined in section 16.2.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: Cement

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

An overview of the APFs of different RPE (according to EN 529:2005) can be found in the glossary of MEASE (16).

Any RPE as defined above shall only be worn if the following principles are implemented in parallel: The duration of work (compare with "duration of exposure" above) should reflect the additional physiological stress for the worker due to the breathing resistance and mass of the RPE itself, due to the increased thermal stress by enclosing the head. In addition, it shall be considered that the worker's capability of using tools and of communicating are reduced during the wearing of RPE. For reasons as given above, the worker should therefore be (i) healthy (especially in view of medical problems that may affect the use of RPE), (ii) have suitable facial characteristics reducing leakages between face and mask (in view of scars and facial hair). The recommended devices above which rely on a tight face seal will not provide the required protection unless they fit the contours of the face properly and securely. The employer and self-employed persons have legal responsibilities for the maintenance and issue of respiratory protective devices and the management of their correct use in the workplace. Therefore, they should define and document a suitable policy for a respiratory protective device programme including training of the workers.

B) Individual protection measures such as personal protection equipment – flue dust and clinker: the

same as the cement.

C) Individual protection measures such as personal protection equipment - grinding aid and reducing

agent: Not relevant because the concentrations of these substances are below the concentration limits set up in the CLP 1272 / 2008 (see point 3).

8.2.3 Environmental exposure controls

Air: Environmental exposure control for the emission of cement particles into air has to be in accordance with the available technology and regulations for the emission of general dust particles.

Water: Do not wash cement into sewage systems or into bodies of water, to avoid high pH. Above pH 9

negative ecotoxicological impacts are possible.

Environmental exposure control is relevant for the aquatic environment as emissions of cements in the different life-cycle stages (production and use) mainly apply to ground and waste water. The aquatic effect and risk assessment covers the effect on organisms/ecosystems due to possible pH changes related to hydroxide discharges. The toxicity of other dissolved inorganic ions is expected to be negligible compared to the potential pH effect.

The pH of effluent and surface water should not exceed 9. Otherwise, it could have an impact on municipal

sewage treatment plants (STPs) and industrial wastewater treatment plants (WWTPs). For that assessment of the exposure, a stepwise approach is recommended:

Tier 1: Retrieve information on effluent pH and the contribution of the cement on the resulting pH. Should the

pH is above 9 and is predominantly attributable to cement, then further actions are required to demonstrate safe use.

Tier 2: Retrieve information on receiving water pH after the discharge point. The pH of the receiving water shall not exceed a value of 9.

Tier 3: Measure the pH in the receiving water after the discharge point. If pH is below 9, safe use is reasonably demonstrated. If pH is found to be above 9, risk management measures have to be implemented: the effluent has to undergo neutralisation, thus ensuring safe use of cement during production or use phase.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: Cement

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

Soil and terrestrial environment: No special emission control measures are necessary for the exposure to the terrestrial environment.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

This information applies to the whole mixture:

- ✓ Appearance: Dry cement is a finely ground solid inorganic material (grey or white powder). Main particle size: 5-30 µm
- ✓ (Odour: Odourless
- ✓ Odour threshold: No odour threshold, odourless
- ✓ pH: (T = 20°C in water, water-solid ratio 1:2): 11-13.5
- ✓ Melting point: > 1 250 °C
- ✓ Initial boiling point and boiling range: Not applicable as under normal atmospheric conditions, melting

point >1 250°C

- ✓ Flash point: Not applicable as is not a liquid
- ✓ Evaporation rate: Not applicable as is not a liquid
- ✓ Flammability (solid, gas): Not applicable as is a solid which is non combustible and does not cause or

contribute to fire through friction

- ✓ Upper/lower flammability or explosive limits: Not applicable as is not a flammable gas
- ✓ Vapour pressure: Not applicable as melting point > 1250 °C
- ✓ Vapour density: Not applicable as melting point > 1250 °C
- ✓ Relative density: 2.75-3.20;
- ✓ Apparent density: 0.9-1.5 g/cm³
- ✓ Solubility(ies) in water (T = 20 °C): slight (0.1-1.5 g/l)
- ✓ Partition coefficient: n-octanol/water: Not applicable as is inorganic mixture.
- ✓ Auto-ignition temperature: Not applicable.
- ✓ Decomposition temperature: Not applicable as no organic peroxide present
- ✓ Viscosity: Not applicable as not a liquid
- ✓ Explosive properties: Not applicable. Not explosive or pyrotechnic. Not in itself capable by chemical

reaction of producing gas at such temperature and pressure and at such a speed as to cause damage to the

surroundings. Not capable of a self-sustaining exothermic chemical reaction.

- ✓ Oxidising properties: Not applicable as does not cause or contribute to the combustion of other materials
- ✓

9.2 Other information

Not applicable.

10. STABILITY AND REACTIVITY

10.1 Reactivity

When mixed with water, cements will harden into a stable mass that is not reactive in normal environments.

10.2 Chemical stability

Dry cements are stable as long as they are properly stored (see Section 7) and compatible with most other

building materials. They should be kept dry.

Contact with incompatible materials should be avoided.

Wet cement is alkaline and incompatible with acids, with ammonium salts, with aluminium or other non-noble

metals. Cement dissolves in hydrofluoric acid to produce corrosive silicon tetrafluoride gas.

Cement reacts

with water to form silicates and calcium hydroxide. Silicates in cement react with powerful oxidizers such as

fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: **Cement**

Revised version: 1/1 June, 2017 Print date: 20 June, 2017
1/2 October 2019

10.3 Possibility of hazardous reactions

Cements do not cause hazardous reactions.

10.4 Conditions to avoid

Humid conditions during storage may cause lump formation and loss of product quality.

10.5 Incompatible materials

Acids, ammonium salts, aluminium or other non-noble metals. Uncontrolled use of aluminium powder in wet cement should be avoided as hydrogen is produced.

10.6. Hazardous decomposition products

Cements will not decompose into any hazardous products.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects – cement, clinker and flue dust

Hazard class	Cat	Effect	Reference
Acute toxicity - dermal	-	Limit test, rabbit, 24 hours contact, 2,000 mg/kg body weight – no lethality. Based on available data, the classification criteria are not met.	(2)
Acute toxicity- inhalation	-	No acute toxicity by inhalation observed. Based on available data, the classification criteria are not met	(9)
Acute toxicity - oral	-	No indication of oral toxicity from studies with cement kiln dust. Based on available data, the classification criteria are not met	Literature survey
Skin corrosion/ irritation	2	Cement in contact with wet skin may cause thickening, cracking or fissuring of the skin. Prolonged contact in combination with abrasion may cause severe burns.	(2) Human experience

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: Cement

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

Serious eye damage/irritation	1	<p>Portland cement clinker caused a mixed picture of corneal effects and the calculated irritation index was 128.</p> <p>Common cements contain varying quantities of Portland cement clinker, fly ash, gypsum, natural pozzolans and limestone.</p> <p>Direct contact with cement may cause corneal damage by mechanical stress, immediate or delayed irritation or inflammation. Direct contact by larger amounts of dry cement or splashes of wet cement may cause effects ranging from moderate eye irritation (e.g. conjunctivitis or blepharitis) to chemical burns and blindness.</p>	(10), (11)
Skin sensitisation	1B	<p>Some individuals may develop eczema upon exposure to wet cement dust, caused either by the high pH which induces irritant contact dermatitis after prolonged contact, or by an immunological reaction to soluble Cr (VI) which elicits allergic contact dermatitis.</p> <p>The response may appear in a variety of forms ranging from a mild rash to severe dermatitis and is a combination of the two above mentioned mechanisms.</p> <p>If the cement contains a soluble Cr (VI) reducing agent and as long as the mentioned period of effectiveness of the chromate reduction is not exceeded, a sensitising effect is not expected [Reference (3)].</p>	(3), (4), (17)
Respiratory sensitisation	-	<p>There is no indication of sensitisation of the respiratory system.</p> <p>Based on available data, the classification criteria are not met</p>	(1)
Germ cell mutagenicity	-	<p>No indication.</p> <p>Based on available data, the classification criteria are not met</p>	(12), (13)
Carcinogenicity		<p>No causal association has been established between cement exposure and cancer.</p>	(1)

	-	<p>The epidemiological literature does not support the designation of cement as a suspected human carcinogen</p> <p>Cement is not classifiable as a human carcinogen (According to ACGIH A4: Agents that cause concern that they could be carcinogenic for humans but which cannot be assessed)</p>	(14)
--	---	---	------

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: Cement

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

		<p>conclusively because of a lack of data. In vitro or animal studies do not provide indications of carcinogenicity that are sufficient to classify the agent with one of the other notations.).</p> <p>Based on available data, the classification criteria are not met.</p>
Reproductive toxicity;	-	Based on available data, the classification criteria are not met.
STOT single exposure	3	<p>Cement dust may irritate the throat and respiratory tract. Coughing, sneezing, and shortness of breath may occur following exposures in excess of occupational exposure limits.</p> <p>Overall, the pattern of evidence clearly indicates that occupational exposure to cement dust has produced deficits in respiratory function. However, evidence available at the present time is insufficient to establish with any confidence the dose-response relationship for these effects.</p>
STOT repeated exposure	-	<p>There is an indication of COPD. The effects are acute and due to high exposures. No chronic effects or effects at low concentration have been observed.</p> <p>Based on available data, the classification criteria are not met</p>
Aspiration hazard	-	Not applicable as cement is not used as an aerosol.

Apart from skin sensitisation, Portland cement clinker and common cements have the same toxicological and eco-toxicological properties.

Information on toxicological effects of grinding aid and reducing agent:

Not relevant because the concentrations of these substances are below the concentration limits set up in the CLP 1272 / 2008 (see point 3).

Medical conditions aggravated by exposure

Inhaling cement dust may aggravate existing respiratory system disease(s) and/or medical conditions such as emphysema or asthma and/or existing skin and/or eye conditions.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

The product is not hazardous to the environment. Ecotoxicological tests with Portland cement on *Daphnia magna* [Reference (5)] and *Selenastrum coli* [Reference (6)] have shown little toxicological impact. Therefore LC50 and EC50 values could not be determined [Reference (7)]. There is no indication of sediment phase toxicity [Reference (8)]. The addition of large amounts of cement to water may, however, cause a rise in pH and may, therefore, be toxic to aquatic life under certain circumstances.

12.2 Persistence and degradability

Not relevant as cement is an inorganic material. After hardening, cement presents no toxicity risks.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: **Cement**

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

12.3 Bioaccumulative potential

Not relevant as cement is an inorganic material. After hardening, cement presents no toxicity risks.

12.4 Mobility in soil

Not relevant as cement is an inorganic material. After hardening, cement presents no toxicity risks.

12.5 Results of PBT and vPvB assessment

Not relevant as cement is an inorganic material. After hardening, cement presents no toxicity risks.

12.6 Other adverse effects

Not relevant.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Do not dispose of into sewage systems or surface waters.

Product - cement that has exceeded its shelf life

EWC entry: 10 13 99 (wastes not otherwise specified).

(and when demonstrated that it contains more than 0.0002% soluble Cr (VI): shall not be used/sold other than for use in controlled closed and totally automated processes or should be recycled or disposed of according to local legislation or treated again with a reducing agent.

Product - unused residue or dry spillage

EWC entry: 10 13 06 (Other particulates and dust).

Pick up dry unused residue or dry spillage as is. Mark the containers. Possibly reuse depending upon shelf life considerations and the requirement to avoid dust exposure. In case

of disposal, harden with water and dispose according to "Product – after addition of water, hardened".

Product – slurries

Allow to harden, avoid entry in sewage and drainage systems or into bodies of water (e.g. streams) and dispose of as explained below under "Product - after addition of water, hardened".

Product - after addition of water, hardened

Dispose of according to the local legislation. Avoid entry into the sewage water system. Dispose of the hardened product as concrete waste. Due to the inertisation, concrete waste is not a dangerous waste.

EWC entries: 10 13 14 (waste from manufacturing of cement – waste concrete or concrete sludge) or 17 01 01 (construction and demolition wastes - concrete).

Packaging

EWC entry: 15 01 01 (waste paper and cardboard packaging).

Completely empty the packaging should be thrown out in the bins for waste paper or to be treated in accordance with local legislation.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: Cement

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

14. TRANSPORT INFORMATION

Cement is not covered by the international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID), therefore no classification is required. No special precautions are needed apart from those mentioned under Section 8.

14.1 UN number

Not relevant

14.2 UN proper shipping name

Not relevant

14.3 Transport hazard class(es)

Not relevant

14.4 Packing group

Not relevant

14.5 Environmental hazards

Not relevant

14.6 Special precautions for user

Not relevant

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not relevant

15. REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Cement is a mixture according to REACH and is not subject to registration. Cement clinker is exempt from registration (Art 2.7 (b) and Annex V.10 of REACH).

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII point 47 Chromium VI compounds).

National legislation:

Ordinance on classification, labelling and packaging of chemical substances and mixture (in force as of 31.08.2010).

Ordinance No.13 /2003 regulates the workers' protection from risks related with workplace exposure to harmful chemical agents Waste management act and its regulations.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out for this mixture by the supplier.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: *Cement*

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

16. OTHER INFORMATION**16.1 Indication of changes**

Format complies with Regulation (EC) No 1907/2006 (REACH) and its amendment Regulation № 453/2010.

Mixture is classified according to the Regulation CLP (EC) № 1272/2008, Regulation 1907/2006 CEE and its Amendments.

Changes in section: Version: 1/1 June,2015

16.2 Identified uses and use descriptors and categories

The table below gives an overview of all relevant identified uses of cement or cement containing hydraulic

binders. All the uses have been grouped in these identified uses because of the specific conditions of

exposure for human health and environment. For each specific use, a set of risk management measures or

localised controls has been derived (see section 8) which need to be put in place by the user of cement or cement containing hydraulic binders to bring the exposure to an acceptable level.

Identified uses of the mixture – cement

PROC	Identified Uses - Use Description	Manufacture/ Formulation of building and materials	Professional/ Industrial use of construction
2	Use in closed, continuous process with occasional controlled exposure, eg industrial or professional manufacture of hydraulic binders	X	X
3	Use in closed batch process, eg industrial or professional manufacture of ready-mix concrete	X	X
5	Mixing or blending in batch process for formulation of mixtures and articles, eg industrial or professional manufacture of pre-cast concrete	X	X
7	Industrial spraying, eg industrial use of wet suspensions of hydraulic binders by spraying		X

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: *Cement*

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

8a	Transfer of substance or mixture from/to vessels/large containers at non-dedicated facilities, eg use of cement in bags to prepare mortar		X
8b	Transfer of substance or mixture from/to vessels/large containers a	X	X

	dedicated facilities, eg filling of silos, trucks or barges at cement plants		
9	Transfer of substance or mixture into small containers, eg filling of cement bags in cement plants	X	X
10	Roller application or brushing, eg products to improve adherence between building surfaces and finishing products		X
11	Non-Industrial spraying, eg professional use of wet suspensions of hydraulic binders by spraying		X
13	Treatment of articles by dipping and pouring, eg covering of construction products with a layer to improve the performance of the product		X
14	Production of mixtures or articles by tableting, compression extrusion, pelletisation, eg production of floor tiling	X	X
19	Hand-mixing with intimate contact and only PPE available, eg mixture of wet hydraulic binder on a construction site		X

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: **Cement**

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

22	Potentially closed processing operations with minerals/metals at		X
----	--	--	---

	elevated temperature in industrial setting, eg production of bricks		
26	Handling of solid inorganic substances at ambient temperature, eg mixture of wet hydraulic binders	X	X

Identified uses of substances in the mixture

A) Identified uses for portland cement clinker and flue dust - the same as the mixture.

B) Grinding aid and reducing agent – Not relevant because the concentrations of these substances are

below the concentration limits set up in the CLP 1272 / 2008 (see point 3).

16.3. Abbreviations and acronyms

ACGIH	American Conference of Industrial Hygienists
ADR/RID	European Agreements on the transport of Dangerous goods by Road/Railway
APF	Assigned protection factor
CAS	Chemical Abstracts Service
CLP	Classification, labelling and packaging (Regulation (EC) No 1272/2008)
COPD	Chronic Obstructive Pulmonary Disease
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
ECHA	European Chemicals Agency
EINECS	European INventory of Existing Commercial chemical Substances
EPA	Type of high efficiency air filter
ES	Exposure scenario
EWC	European Waste Catalogue
FF P	Filtering facepiece against particles (disposable)
FM P	Filtering mask against particles with filter cartridge
HEPA	Type of high efficiency air filter
H&S	Health and Safety
IATA	International Air Transport Association
IMDG	International agreement on the Maritime transport of Dangerous GoodsLC50 Median lethal dose
MEASE	Metals estimation and assessment of substance exposure, EBRC Consulting GmbH for Eurometaux, http://www.ebrc.de/industrial-chemicals-reach/projects-andreferences/mease.php
MS	Member State
OELV	Occupational exposure limit value

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: **Cement**

Revised version: 1/1 June, 2017 Print date: 20 June, 2017
1/2 October 2019

PBT	Persistent, bio-accumulative and toxic
PNEC	Predicted no-effect concentration
PROC	Process category
RE	Repeated exposure
REACH	Registration, Evaluation and Authorisation of Chemicals
RPE	Respiratory protective equipment
SCOEL	Scientific Committee on Occupational Exposure Limit Values
SDS	Safety Data Sheet
SE	Single exposure
STP	Sewage treatment plant
STOT	Specific Target Organ Toxicity
TLV-TWA	Threshold Limit Value-Time-Weighted Average
TRGS	Technische Regeln für Gefahrstoffe
VLE-MP	Exposure limit value-weighted average in mg by cubic meter of air
vPvB	Very persistent, very bio-accumulative
w/w	Weight by weight
WWTP	Waste water treatment plant
LC50	Lethal concentration

16.4 Key literature references and sources of data

(1) *Portland Cement Dust - Hazard assessment document EH75/7*, UK Health and Safety Executive, 2006.

Available from: <http://www.hse.gov.uk/pubns/web/portlandcement.pdf>.

(2) *Observations on the effects of skin irritation caused by cement*, Kietzman et al, *Dermatosen*, 47, 5, 184-189 (1999).

(3) *European Commission's Scientific Committee on Toxicology, Ecotoxicology and the Environment*

(SCTEE) *opinion of the risks to health from Cr (VI) in cement* (European Commission, 2002).
http://ec.europa.eu/health/archive/ph_risk/committees/sct/documents/out158_en.pdf.

(4) *Epidemiological assessment of the occurrence of allergic dermatitis in workers in the construction industry related to the content of Cr (VI) in cement*, NIOH, Page 11, 2003.

(5) *U.S. EPA, Short-term Methods for Estimating the Chronic Toxicity of Effluents and Receiving Waters to*

Freshwater Organisms, 3rd ed. EPA/600/7-91/002, Environmental Monitoring and Support Laboratory, U.S. EPA, Cincinnati, OH (1994a) and 4th ed. EPA-821-R-02-013, US EPA, office of water, Washington D.C. (2002).

(6) *U.S. EPA, Methods for Measuring the Acute Toxicity of Effluents and Receiving Waters to Freshwater and Marine Organisms*, 4th ed. EPA/600/4-90/027F, Environmental Monitoring and Support Laboratory, U.S.

EPA, Cincinnati, OH (1993) and 5th ed. EPA-821-R-02-012, US EPA, office of water, Washington D.C. (2002).

(7) *Environmental Impact of Construction and Repair Materials on Surface and Ground Waters. Summary of Methodology, Laboratory Results, and Model Development.* NCHRP report 448, National Academy Press, Washington, D.C., 2001.

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: **Cement**

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

(8) *Final report Sediment Phase Toxicity Test Results with Corophium volutator for Portland clinker* prepared for Norcem A.S. by AnalyCen Ecotox AS, 2007.

(9) TNO report V8801/02, *An acute (4-hour) inhalation toxicity study with Portland Cement Clinker CLP/GHS 03-2010-fine in rats*, August 2010.

(10) TNO report V8815/09, *Evaluation of eye irritation potential of cement clinker G in vitro using the isolated chicken eye test*, April 2010.

(11) TNO report V8815/10, *Evaluation of eye irritation potential of cement clinker W in vitro using the isolated chicken eye test*, April 2010.

(12) *Investigation of the cytotoxic and proinflammatory effects of cement dusts in rat alveolar macrophages*,
Van Berlo et al, Chem. Res. Toxicol., 2009 Sept; 22(9):1548-58.

(13) *Cytotoxicity and genotoxicity of cement dusts in A549 human epithelial lung cells in vitro*;
Gminski et al,
Abstract DGPT conference Mainz, 2008.

(14) *Comments on a recommendation from the American Conference of governmental industrial Hygienists to change the threshold limit value for Portland cement*, Patrick A. Hessel and John F. Gamble, EpiLung Consulting, June 2008.

(15) *Prospective monitoring of exposure and lung function among cement workers, Interim report of the study after the data collection of Phase I-II 2006-2010*, Hilde Notø, Helge Kjuus, Marit Skogstad and Karl-Christian Nordby, National Institute of Occupational Health, Oslo, Norway, March 2010.

(16) MEASE, Metals estimation and assessment of substance exposure, EBRC Consulting GmbH for Eurometaux, <http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php>.

(17) *Occurrence of allergic contact dermatitis caused by chromium in cement. A review of epidemiological investigations*, Kåre Lenvik, Helge Kjuus, NIOH, Oslo, December 2011.

16.5 Training advice

In addition to health, safety and environmental training programs for their workers, companies must ensure that workers read, understand and apply the requirements of this SDS.

16.6 Further information

See Annex(es) for the ES of the following substances:

Main information from ES of the substances in the mixture was included in the section 1,2,3,8,12.

16.7 Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) adapted to AI-MESP 18 /2017

Product: Cement

Revised version: 1/1 June, 2017 Print date: 20 June, 2017

1/2 October 2019

1/3 June 2025

Classification according to Regulation (EC) No. 1272/2008	Classification procedure
Skin Irrit. 2, H315	On basis of test data
Eye dam. 1, H318	On basis of test data
Skin sens. 1B, H317	Human experience
STOT SE. 3, H335	Human experience

16.8 Disclaimer

The information on this data sheet reflects the currently available knowledge and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product, including the use of the product in combination with any other product or any other process, is the responsibility of the user.

It is implicit that the user is responsible for determining appropriate safety measures and for applying the legislation covering his/her own activities.

Valid since: 20 June, 2017.

Last version October 2019 according to AI-MESP 18/2017